

Speed & Feed Guide

Series 1130

Fusion | 4FL | Square

Profiling			SFM based on RDOC					IPT *(BASELINE)									
			Cutting Diameter Engaged					Cutting Diameter									
Material			Hardness	5%	10%	20%	30%	50%	*1/8	*3/16	*1/4	5/16	3/8	1/2	5/8	3/4	1
P	Steel	Free Machining & Low Carbon: 10XX, 11XX, 12XX, A36	≤ 28 Rc	1050	700	385	375	350	0.00065	0.00097	0.00120	0.032	0.0038	0.0054	0.0065	0.0076	0.0108
	Steel	Medium/High Carbon Steels, Alloy Steels: 13XX, 41XX, 43XX, 86XX	28-38 Rc	630	420	320	250	210	0.00065	0.00097	0.00120	0.0032	0.0038	0.0054	0.0065	0.0076	0.0108
	Die Steels	A2, H13, L6, P20, S7	28-44 Rc	525	350	300	275	250	0.00065	0.00097	0.00120	0.0032	0.0038	0.0054	0.0065	0.0076	0.0108
M	Stainless Steels	Ferritic	≤ 28 Rc	650	600	550	500	450	0.00065	0.00097	0.00120	0.0032	0.0038	0.0054	0.0065	0.0076	0.0108
	Stainless Steels	Martensitic	≤ 28 Rc	525	400	350	300	250	0.00065	0.00097	0.00120	0.0032	0.0038	0.0054	0.0065	0.0076	0.0108
	Stainless Steels	Difficult to Machine, 302B, 304B, 309, 310, 316, 316Ti, PH13-8Mo	> 28 Rc	525	400	350	300	250	0.00065	0.00097	0.00120	0.0032	0.0038	0.0054	0.0065	0.0076	0.0108
S	Super Alloys	High Temp, Nimonic, Inconel, Monel, Hastelloy	≤ 42 Rc	265	200	175	150	100	0.00048	0.00065	0.00096	0.0017	0.0019	0.0028	0.0032	0.0038	0.0054
	Super Alloys	Titanium: Ti 3Al-2.5V, Ti 6Al-4V Ti 10V-2Fe-3Al	≤ 42 Rc	230	200	175	150	125	0.00048	0.00065	0.00096	0.0017	0.0019	0.0028	0.0032	0.0038	0.0054
H	Hardened Steels	Tool Steel, Die Steel: S7, H13, A2	45-55 Rc	250	240	230	210	200	0.00360	0.00432	0.00504	0.0022	0.0025	0.0036	0.0043	0.0050	0.0072
K	Cast-Iron	Gray: SAE J431, ASTM A48	≤ 240 HB	425	400	375	350	300	0.00065	0.00097	0.00120	0.0032	0.0038	0.0054	0.0065	0.0076	0.0108
	Cast-Iron	Ductile & Malleable, ASTM A536, ASTM 897, ASTM A47, ASTM A220, ASTM A602	> 240 HB	320	300	250	225	200	0.00065	0.00097	0.00120	0.0032	0.0038	0.0054	0.0065	0.0076	0.0108
N	Non-Ferrous	Aluminum, Brass, Bronze, Copper, Plastics, Graphite	-	1000	960	920	880	840	0.00048	0.00065	0.00096	0.0032	0.0038	0.0054	0.0065	0.0076	0.0108

Slotting			SFM			IPT *(BASELINE)									
			Cutting Diameter Engaged			Cutting Diameter									
Material			Hardness	25%	50%	100%	*1/8	*3/16	*1/4	5/16	3/8	1/2	5/8	3/4	1
P	Steel	Free Machining & Low Carbon: 10XX, 11XX, 12XX, A36	≤ 28 Rc	462	444	420	0.00060	0.00084	0.00120	0.0019	0.0023	0.0037	0.00046	0.0046	0.0060
	Steel	Medium/High Carbon Steels, Alloy Steels: 13XX, 41XX, 43XX, 86XX	28-38 Rc	294	276	262	0.00048	0.00084	0.00108	0.0019	0.0023	0.0030	0.0037	0.0046	0.0060
	Die Steels	A2, H13, L6, P20, S7	28-44 Rc	252	234	210	0.00048	0.00072	0.00096	0.0019	0.0023	0.0030	0.0037	0.0046	0.0060
M	Stainless Steels	Ferritic	≤ 28 Rc	462	444	420	0.00060	0.00084	0.00120	0.0019	0.0023	0.0030	0.0037	0.0046	0.0060
	Stainless Steels	Martensitic	≤ 28 Rc	294	252	210	0.00048	0.00084	0.00120	0.0019	0.0023	0.0030	0.0037	0.0046	0.0060
	Stainless Steels	Difficult to Machine, 302B, 304B, 309, 310, 316, 316B, 316L, 316Ti, 317, 317L, 321, PH13-8Mo, Nitronics	> 28 Rc	252	234	210	0.00036	0.00048	0.00060	0.0019	0.0023	0.0030	0.0037	0.0046	0.0060
S	Super Alloys	High Temp, Nimonic, Inconel, Monel, Hastelloy	≤ 42 Rc	150	126	108	0.00036	0.00048	0.00060	0.0010	0.0012	0.0016	0.0019	0.0020	0.0031
	Super Alloys	Titanium: Ti 3Al-2.5V, Ti 6Al-4V Ti 10V-2Fe-3Al	≤ 42 Rc	120	108	96	0.00036	0.00048	0.00060	0.0010	0.0012	0.0016	0.0019	0.0020	0.0031
H	Hardened Steels	Tool Steel, Die Steel: S7, H13, A2	34-45 Rc	294	276	252	0.00024	0.00036	0.00048	0.0019	0.0023	0.0030	0.0037	0.0046	0.0060
K	Cast Iron	Gray: SAE J431, ASTM A48	≤ 240 HB	540	480	420	0.00060	0.00084	0.00120	0.0019	0.0023	0.0030	0.0037	0.0046	0.0060
	Cast Iron	Ductile & Malleable, ASTM A536, ASTM 897, ASTM A47, ASTM A220	> 240 HB	360	300	270	0.00048	0.00084	0.00108	0.0019	0.0023	0.0030	0.0037	0.0046	0.0060
N	Non-Ferrous	Aluminum, Brass, Bronze, Copper, Plastics, Graphite	-	900	720	540	0.00132	0.00204	0.00264	0.0019	0.0023	0.0030	0.0037	0.0046	0.0060